

proPERLA[®] Wood Impregnator is a water based water repellent based on the latest nanotechnology, that can be used on all wood surfaces on walls, roofs and floors. proPERLA[®] is a special chemical composition that reacts and actively bond to wood surfaces.

Recommended for:

All wood surfaces.

Apply directly on surfaces less than one year old. Older surfaces must first be cleaned thoroughly with a pressure washer or deepEX Powerbrush before treatment.

Preparation

The surface needs to be dry, clean and free from contamination.

Application

Use low-pressure pump, sprayer, brush or roller. A minimum temperature of 5 °C is needed.

Recommendation

Always make a test coat to ensure the compatibility of product and surface.

Coverage rate

100-200 ml per m² depending on surface porosity

Equipment care

Cleaned up in water directly after use.

Storage

Store dry and frost-free. Keep out of reach of children.

Shelf life

24 months (in original sealed container).

Packing sizes

Can 5 litres.

Colour

Colourless when applied.

Thinning

Undiluted.

Drying time

Approx. 1 hour at 20° C and 60% RH.

Properties and Advantages

- Based on the latest technology.
- Scientifically engineered to protect wood surfaces by active binding.
- Specifically designed for roofs, walls and floors.
- Extremely water repellent and self-cleaning.
- Obstructs discoloration
- Minimizes shrinkage.
- Reduces growth of microorganisms.



This BECO TREAT ApS information was compiled according to the state of the art and our present experience. It is intended to support craftsmen in selecting the proper materials and using them correctly. The information provided here does not release the user from the responsibility for checking the material for its suitability for the intended application, considering all object-related factors. New editions replace the information given here.
Status: May 2013